

## Amendments to the Claims:

1. (currently amended) A table comprising:

a main support section having a first main support vertical member having a first and a second end, a second main support vertical member having a first and a second end, a first main support horizontal member having a first end attached to said first end of said first main support vertical member and a second end attached to said first end of said second main support vertical member, and a second main support horizontal member having a first end attached to said second end of said first main support vertical member and a second end attached to said second end of said second main support vertical member;

a first side support section having a first side first vertical member having a first and a second end, a first side second vertical member having a first and a second end, a first side first horizontal member having a first end attached to said first end of said first side first vertical member and a second end attached to said first end of said first side second vertical member, and a first side second horizontal member having a first end attached to said second end of said first side first vertical member and a second end attached to said second end of said first side second vertical member, said first side first vertical member pivotably connected to said first main support vertical member to enable pivoting of said first side support section between a first position parallel and closely adjacent said main support section and a second position generally perpendicular to said main support section;

a second side support section having a second side first vertical member having a first and a second end, a second side second vertical member having a first and a second end, a second side first horizontal member having a first end attached to said first end of said second side first vertical member and a second end attached to said first end of said second side second vertical member, and a second side second horizontal member having a first end attached to said second end of said second side first vertical member and a second end attached to said second end of said second side second vertical member, said second side first vertical member pivotably connected to said second main support vertical member to enable pivoting of said second side support section between a first position parallel and closely adjacent said main support section and a second position generally perpendicular to said main support section;

an upper support member pivotably attached to said second main support horizontal member to enable pivoting of said upper support section member between a first position supported by said main support and said first and said second side supports, and a second position adjacent and generally parallel said first and second side supports, supported by said main support.

2.(original) The table as recited in claim 1 and further comprising an engagement structure carried by said upper support member for locking said upper support member to one of said first and said second side support sections in said first position, and for locking said upper support member to said main support in said second position.

3.(currently amended) The table as recited in claim 2 wherein said engagement structure further comprises:

a base portion attached to said upper ~~main~~ support ~~horizontal~~ member;

an extension portion attached to said ~~based~~ base portion and having a lateral notch for facilitating engagement locking.

4.(original) The table as recited in claim 1 wherein said an upper support member and said main support create a space within which at least half of said first and said second side supports fit when said upper support member is placed in said second position adjacent and generally parallel said first and second side supports, and said main support.

5.(original) The adjustable table as recited in claim 1 wherein said first and second main support vertical members and said first and second side first vertical members all have open first ends and further comprising leg extensions fittable in said open ends, said leg extensions are fixable within said first ends of said first and second main support vertical members and said first and second side first vertical members.